

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: ST002-00C UPC# 7 73204 60002 3

Product Name: **Filler Stick (Universal White)**
Product Use: Paint filler stick
Effective date: August 2008
Revision Date: August 2009

Company Identification

Distributed by: Alexandria Moulding, Inc.
 95 Lochiel Street East
 Alexandria, Ontario K0C-1A0
 Phone: 1-866-377-2539

**FOR EMERGENCY MEDICAL
INFORMATION, CONTACT LOCAL
POISON CONTROL OFFICE.**

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure

- Inhalation
- Ingestion
- Skin absorption

Eye Contact:

- Moderate eye irritation

Skin Contact:

- Can cause skin irritation.

Ingestion:

- Irritation of the mouth, throat, and stomach.
- Can be harmful if swallowed.

Inhalation:

- Can cause respiratory tract irritation.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name	CAS Number
This product contains no hazardous materials			

If this section is blank there are no hazardous components per WHMIS guidelines.

4. FIRST AID MEASURES

Eye Contact:

Flush with running water for 15 minutes, holding lid open to expose surface of eye, contact physician.

Skin Contact:

Remove contaminated clothing and shoes, wash with mild soap and water.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING, contact physician, poison control center, or hospital emergency room immediately. If victim is conscious, give a glassful of water or milk. Never give anything by mouth to an unconscious person.

Inhalation:

If affected by vapors or spray mists, remove to fresh air at once. Apply artificial respiration if necessary, contact physician immediately.

5. FIRE FIGHTING MEASURES

Flammability Class:	IIIB
Flash point (Fahrenheit):	>460 °F (Open cup method)
Lower explosive limit:	N/A
Upper explosive limit:	N/A
Autoignition temperature:	not determined -°F (°C)
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

Unusual fire and explosion hazards:

Pressure may develop in closed containers if overheated.

Extinguishing media:

Foam, dry chemical, carbon dioxide. Water is not suitable as an extinguishing media but may be used to cool nearby containers.

Fire fighting procedures:

Fire fighters should wear normal protective equipment and positive pressure breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Remove ignition sources. Dike and take up with absorbent material. Ensure adequate ventilation, avoid build up of vapors.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep containers closed when not in use. Do not use or store near open flame, sources of ignition, or strong oxidizers.

Avoid breathing vapors or spray mists. Avoid prolonged or repeated personal contact. Wash thoroughly after use.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Face shield or safety glasses are recommended.

Skin protection:

Use chemical resistant gloves when necessary to protect from personal exposure.

Other Personal Protection Data:

Protective clothing should be used as necessary to protect from personal exposure.

Respiratory protection:

None required in normal use.

Ventilation

Control airborne concentration below exposure guidelines. Local exhaust ventilation may be necessary.

Exposure Guidelines

None available.

9. PHYSICAL PROPERTIES

Physical State:	Solid
pH:	not determined
Vapor pressure:	not determined
Vapor density (air = 1.0):	Heavier than air.
Boiling point:	not determined
Solubility in water:	not determined
Density (lbs per US gallon):	8.3 typical
Specific Gravity:	0.99 typical
Evaporation rate (butyl acetate = 1.0):	slower than ether
Flash point (Fahrenheit):	not determined
Lower explosive limit:	not determined
Upper explosive limit:	not determined
Autoignition temperature:	not determined -°F (°C)
Percent Volatile:	0
C.A.R.B. VOC:	0%

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Exposure to high heat, sparks, open flame or other sources of ignition.
Incompatibility:	Strong oxidizers like chlorine.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Fumes, smoke, other unknown organic oxides are possible.
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Flammability Class:	IIIB

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
None		

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Dispose of waste in accordance with all applicable state, local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

DOT Information	UN Number: Classification : Proper Shipping Name : Packing Group : Exceptions :	None assigned by DOT Not considered hazardous by DOT None assigned by DOT None assigned by DOT 49CFR §173.150 (ORM-D) may be applicable in domestic ground transportation of flammable liquids (Class 3) in some product sizes.
------------------------	--	---

15. REGULATORY INFORMATION

None at this time

16. OTHER INFORMATION

HMIS Codes

Health:	1
Flammability:	1
Reactivity:	0
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH -National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH – American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, TLV – Threshold Limit Value, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Alexandria Moulding assumes no obligation or liability for use of this information. UNLESS ALEXANDRIA MOULDING AGREES OTHERWISE IN WRITING, ALEXANDRIA MOULDING MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. ALEXANDRIA MOULDING WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.